

DIAMOND 10[™] Coated Homogeneous Sheet

MEDINPRO®

NOH HOW MOH HOW WOH HO

Inspiring Great Spaces





Tough as Diamond

- Unique formulation with industrial diamond More compacted and tougher coating to protect the vinyl flooring





Easy to Clean

- Water/oil-based pollutants are difficult to penetrate into flooring
- More economic and quicker cleaning maintenace



More Durable

- Superb anti-scratching capability
- Double the average coating thickness of competitors
- Excellent user experience in durability



Anti-Chemical

- Prevent kinds of medicament and strong acid/alkali from damage to flooring
- Tolerate to daily repeated detergent treatment



The soft palette of this homogeneous product works well in medical environments and is designed for sterile and aseptic areas. with the combination of Medintone's homogeneous construction and unique Diamond 10™ technology, it is the perfect solution for your high-traffic area where cleanliness, durability, maintenance are the focus.













Blue Waves

K821A-630 WR:W821-630



K821A-622 WR:W821-622



K821A-637 WR:W821-637

Porcelain



K821A-507 WR:W821-507



K821A-602 WR:W821-602



Etemal



K821A-619 WR:W821-619



K821A-623 WR:W821-623







K821A-521 Bamboo WR:W821-521



K821A-618 WR:W821-618

Night Sky

Sparrow

K821A-508 WR:W821-508

Shlyama

K821A-529 WR:W821-529







K821A-127

WR:W821-127

K821A-128

WR:W821-128







Bakasana

K821A-005

WR:W821-005

Graphite

K821A-006

WR:W821-006

Particle

Inspiring Great Spaces™



Technical Data			
Characteristics	Standard	Unit	Result
Type of flooring	ISO 10581/EN 649		Homogeneous Sheet
Material			Polyvinyl chloride
Coating			DIAMOND 10 TM
Safety criteria			
Flammability	EN 13501-1	class	Bfl-s1
Dynamic coefficient of friction	EN 13893	class	DS
DOP content	EN 15777		Pass
Impact sound reduction	ISO 10140	dB	3
	ISO 717-2		
Performance behaviour			
Sheet width	ISO 24341-EN 426	m	2
Sheet length	ISO 24341-EN 426	m	13-20
Overall thickness	ISO 24346-EN 428	mm	2.0
Total weight	ISO 23997-EN 430	kg/m²	2.69
Wear resistance	EN 649	group	Т
Binder content	EN ISO 10581	Туре	Type1
Dimensional stability	ISO 23999-EN 434	E:	X:<0.4%; Y:<0.4%
Color fastness	ISO 105-B02	rating	≥6
Resistance to staining	EN 423		No Stain 0
Classification			
Domestic	ISO 10874-EN 685	class	23 heavy duty
Commercial	ISO 10874-EN 685	class	34 very heavy duty
Industrial	ISO 10874-EN 685	class	43 heavy duty
Additional property			
Castor Chair 🕝 🗸 Underfloor Hea	ting Antistatic Behavious	✓ Chemical Re	esistance 🛜 🗸 Anti-Betadine 🗸











INDUSTRIAL - HEAVY

























Sample piece in this sample folder is only for color reference, the structure and color of which may be varied in actual product supplying

www.armstrongflooring.asia ARMSTRONG FLOORING OFFICES:

Hong Kong (852) 2585 7800 (852) 2598 7181 (65) 6604 6835 Singapore Malaysia (60) 379 323 331 (60) 379 606 331 (62) 21 2965 7867 (62) 21 2965 7866















